

SIGMA SEPTIC TANK 2800 to 9150 - DECLARATION OF PERFORMANCE

kingspan-clearwater-sigma-septic-2800-9150-dop-en-mar2026-v2

1. Unique identification code of the product-type:

**Wastewater Septic Tank from 2800L to 9150L
STH 2800, STH 3800, STH 4800, STH 5700, STH 7150, STH 9150**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**Shallow Dig Prefabricated Domestic Septic Tank: See CE marking affixed to product
STH (2800L) to STH (9150L)**

3. Intended use/es of the product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

To be used for Collection & Settlement of Wastewater from Domestic applications up to 9150L

4. Manufacturer name, registered trade name or registered trade mark and contact address as required under Article 11(5):

**Kingspan Water & Energy Ltd
College Rd North
Aston Clinton, Aylesbury, Buckinghamshire
HP22 5EW**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System/s of assessment and verification of constancy of performance (AVCP) of the product as set out in CPR, Annex V:

3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN:12566-1:2000/A1:2003

Notified body/ bodies:

Notified Body No: 1739 + PIA Prüfinstitut für Abwassertechnik GmbH

Document date:	Document version no:	ECN no:
13/03/2026	V2.	2326




8. Declared performance/s:

Essential characteristics	Performance	Harmonised technical specification
Structural Behaviour	Confirmed by Pit Test under the following Conditions: - Maximum installation Depth 0m over cover level - Wet conditions maximum water level 2.0m	EN:12566-1:2000/A1:2003
Reaction to fire	Class E	
Water Tightness (water test)	Water Tight (water test)	
Material Durability	Creep Factor $\alpha_{material} = 0,48$ (average value) Ageing Factor (β) = 0,46 (average value)	
Treatment Efficiency	99.70%	
Emission of Dangerous Substances	NPD	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



David Anderson – Water Business Unit Director

At Portadown on 13 March 2026

Document date:	Document version no:	ECN no:
13/03/2026	V2.	2326